



SHELL BUCKLING ANALYSIS REPORT

ENGINEERING ASSESSMENT DOCUMENT

PREPARED BY

Example Aerospace Structures Ltd (fictitious)

Stability and Loads
1 Example Street
Exampleton
United Kingdom
reports@example.com
+44 20 7946 0000
www.example.com

PREPARED FOR

Example Launch Systems Ltd (fictitious)

Propulsion Structures
2 Sample Road
Sampleton
United Kingdom

CONTACT

A. N. Other (fictitious) — Structures Lead
a.n.other@example.org
+44 161 496 0000
Customer no. C-0042
Supplier no. S-0007

Project	LH2 barrel · public VCT geometry (Franzoni 2025)
Project no.	PRJ-2026-017
Customer ref.	ELS-TNK-0001
Order no.	PO-000123
Report no.	EAS-SAMPLE-2026-001
Revision	A
Issue date	8 October 2026
Prepared by	J. Bloggs (fictitious)
Subject	Axial buckling check of an unstiffened LH2 tank barrel: $R = 2701.275$ mm (mid-surface), $L = 3110$ mm, $t = 2.55$ mm, AA2219
Purpose	Public sample report for the barrel shown in the Skalnav demo video. Geometry after Franzoni et al., Aersp. Sci. Technol. 178 (2026) 113063; loads and w/t are illustrative. All company, customer, person and project data are fictitious.
Geometry	cylinder

ASSESSMENT RESULT

Adequate buckling reserve across the current operational envelope.

Minimum RF = **1.57**

Executive Summary

cylinder · 3 load cases · 8 October 2026

SAFE

1.57

minimum RF

governing: LC-2 Axial · NASA SP-8007 · axial buckling

MIN RF 1.57 on LC-2 · NASA SP-8007	GOVERNING LC-2 NASA SP-8007 · axial	FAILURE MODE axial buckling	R/t 1059 Z = 1325
---	--	---	--

RF ENVELOPE

all 3 at or above RF = 1.0 · governing LC-2 · NASA SP-8007 · bars cut at RF 2.0

LC-1 · Skalnav design value		2.94
LC-2 · NASA SP-8007		1.57
LC-3 · ECSS-E-HB-32-24A		1.58

KEY INSIGHTS

Governing LC: LC-2 Axial · NASA SP-8007

axial buckling (RF = 1.57)

All 3 LCs at or above RF = 1.0

Mission load envelope sits within the allowable shell capacity.

Geometry: R/t = 1059, L/R = 1.15

RECOMMENDATION

No corrective action required

CURRENT

min RF 1.57

LC-2 Axial · NASA SP-8007 sits in the safe band (RF >= 1.50) for the loads assessed in this report.

Inputs and method

Every number in this report follows from these inputs.

Geometry, material and imperfection					
Shell	cylinder	R (mid-surface)	2701.275 mm	L	3110 mm
t	2.55 mm	R/t	1059	L/R	1.15
Z (Batdorf)	1325	E	70000 MPa	ν	0.33
f _y	390 MPa	Imperfection	w/t = 1.00		

Load cases					
Load case	Type	Loads	Method	Design capacity	RF
LC-1 Axial · Skalnav design value	axial	F = 240.0 kN	Skalnav design value	705.51 kN	2.94
LC-2 Axial · NASA SP-8007	axial	F = 240.0 kN	NASA SP-8007	377.77 kN	1.57
LC-3 Axial · ECSS-E-HB-32-24A	axial	F = 240.0 kN	ECSS-E-HB-32-24A	379.29 kN	1.58

RF (reserve factor) = design capacity / demand of the load case.

KDF (knockdown factor) = design buckling load / classical (perfect-shell) buckling load.

NASA SP-8007 axial knockdown, as implemented: $\gamma = 1 - 0.902 \cdot (1 - \exp(-\phi))$, $\phi = \sqrt{R/t}/16$. SP-8007-2020 Eq. 9 prints 0.901; at R/t = 1059 the two differ by 0.40 % in γ .

RF bands: below 1.00 fail · 1.00 to below 1.10 critical · 1.10 to below 1.50 marginal · 1.50 and above safe.

Method & assumptions	
Method	Skalnav design value / NASA SP-8007 / ECSS-E-HB-32-24A

Engineering Assessment

3 load cases · selected from the envelope by significance

LC-2 Axial · NASA SP-8007 — Governing load case

GOVERNING GROUND

PARAMETERS

F_axial	240.0 kN	M_bend	—
P_int	0.00 MPa	RF	1.57

ENGINEERING RATIONALE

Ground pure axial-compression load case.

NOTES (MISSION PROFILE)

Ground case, tank unpressurised. Same 240 kN load and barrel inputs as the other rows. NASA SP-8007 design curve as implemented (coefficient 0.902, see Inputs and method), set by R/t alone: KDF 0.2160, design load 377.77 kN.

CONCLUSION

In the safe band; no action required at the loads assessed.

LC-1 Axial · Skalnav design value — Ground load case

RESERVE GROUND

PARAMETERS

F_axial	240.0 kN	M_bend	—
P_int	0.00 MPa	RF	2.94

ENGINEERING RATIONALE

Ground pure axial-compression load case.

NOTES (MISSION PROFILE)

Ground case, tank unpressurised. Model comparison: unstiffened elastic barrel, axial load only, illustrative load (not a vehicle load). Same barrel and inputs as the Skalnav demo video, w/t = 1.00 (illustrative). Skalnav design value: KDF 0.4033, design load 705.51 kN; classical buckling load 1749.18 kN.

CONCLUSION

In the safe band; no action required at the loads assessed.

LC-3 Axial · ECSS-E-HB-32-24A

— Ground load case

RESERVE

GROUND

PARAMETERS

F_axial	240.0 kN	M_bend	—
P_int	0.00 MPa	RF	1.58

ENGINEERING RATIONALE

Ground pure axial-compression load case.

NOTES (MISSION PROFILE)

Ground case, tank unpressurised. Same 240 kN load and barrel inputs as the other rows. ECSS-E-HB-32-24A: KDF 0.2168, design load 379.29 kN.

CONCLUSION

In the safe band; no action required at the loads assessed.

Engineering Responsibility & Scope of Results

Skalnav is a calculation and decision-support tool for qualified professional users. It performs stability verifications according to the standards and methods identified in this report, in the program version stated in the footer. All results are based on the input data entered by the user and on the documented model assumptions.

All input data and all results must be independently reviewed, checked for plausibility, and released by a qualified, professionally competent person before any use. Results must not be used as the sole basis for the design, release, or acceptance of safety-critical components. Responsibility for the selection of the verification method, the interpretation of results, and their structural implementation lies exclusively with the user.

This report does not constitute a review, assessment, approval, certification, or acceptance by Skalnav and does not replace any examination required by law, standard, regulatory order, or the user's internal processes. No representation is made that results or reports will be recognised by any review, approval, or certification body, or that they are suitable for a specific verification or approval purpose of the user.